

BALUSTRADE SYSTEM KITS

Balustrade Solution 3m Clamp Kits (Domestic and Commercial Applications)

BASE FIX (PG120B)

* Doesn't include substrate fixings or end caps

Glass Thickness (Nominal) (System can Accommodate)
12-21.5mm

Area (Ideally suited)

Internal
& External



| Model | Sizes mm | Finish | Material | Type | Application |
|--------|-------------------------|-------------------------------------|---|--|--|
| | GLASS THICKNESS: | | | CHANNEL SYSTEM BASE FIX | POSIGLAZE BASE ANOD BRUSHED DRILLED KIT COMPRISES OF: 1 x 3m Base Drilled Channel 2 x 3m Top Clip Bead 1 x Clamp kit (consisting of 12 clamps) to suit specified glass thickness 1 x Spanner 1 x Dowel Chanel Joiners (Pair) |
| 500036 | 12mm | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED ANODISED TO 20 MICRONS | * Complete with seal strips, gaskets, side cladding and glass clamps | |
| 500037 | 13.5mm | ANOD-BRUSHED | | | |
| 500038 | 15mm | ANOD-BRUSHED | | | |
| 500039 | 17.5mm | ANOD-BRUSHED | | | |
| 500040 | 19mm | ANOD-BRUSHED | | | |
| 500041 | 21.5mm | ANOD-BRUSHED | | | |
| 500248 | 12mm | MILL - FINISH | ALUM 6063 T6 | | |
| 500401 | 13.5mm | MILL - FINISH | | | |
| 500409 | 15mm | MILL - FINISH | | | |
| 500410 | 17.5mm | MILL - FINISH | | | |
| 500404 | 19mm | MILL - FINISH | | | |
| 500405 | 21.5mm | MILL - FINISH | | | |
| | OVERALL LENGTH = 3000mm | ON REQUEST: POWDERCOAT ANOD NATURAL | | | |

SIDE FIX (PG120S)

* Doesn't include substrate fixings or end caps

Glass Thickness (Nominal) (System can Accommodate)
12-21.5mm

Area (Ideally suited)

Internal
& External



| Model | Sizes mm | Finish | Material | Type | Application |
|--------|-------------------------|-------------------------------------|---|--|--|
| | GLASS THICKNESS: | | | CHANNEL SYSTEM SIDE FIX | POSIGLAZE SIDE ANOD BRUSHED DRILLED KIT COMPRISES OF: 1 x 3m Side Drilled Channel 1 x 3m Top Clip Bead 1 x 3m Side Cladding 1 x Clamp kit (consisting of 12 clamps) to suit specified glass thickness 1 x Spanner 1 x Dowel Chanel Joiners (Pair) |
| 500042 | 12 | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED ANODISED TO 20 MICRONS | * Complete with seal strips, gaskets, side cladding and glass clamps | |
| 500043 | 13.5 | ANOD-BRUSHED | | | |
| 500044 | 15 | ANOD-BRUSHED | | | |
| 500045 | 17.5 | ANOD-BRUSHED | | | |
| 500046 | 19 | ANOD-BRUSHED | | | |
| 500047 | 21.5 | ANOD-BRUSHED | | | |
| 500249 | 12 | MILL - FINISH | ALUM 6063 T6 | | |
| 500416 | 13.5 | MILL - FINISH | | | |
| 500418 | 15 | MILL - FINISH | | | |
| 500419 | 17.5 | MILL - FINISH | | | |
| 500421 | 19 | MILL - FINISH | | | |
| 500422 | 21.5 | MILL - FINISH | | | |
| | OVERALL LENGTH = 3000mm | ON REQUEST: POWDERCOAT ANOD NATURAL | | | |

BALUSTRADE SYSTEM KITS

Balustrade Solution 3m Clamp Kits (Domestic and Commercial Applications)

ANGLED SIDE FIX (PG180S)

* Doesn't include substrate fixings or end caps

Glass Thickness (Nominal) (System can Accommodate)

12-21.5mm

Area (Ideally suited)

Internal
& External















| Model | Sizes mm | Finish | Material | Type | Application | |
|--------|-------------------------|--|--|--|---|---|
| | GLASS THICKNESS: | | | CHANNEL SYSTEM SIDE FIX | POSIGLAZE SIDE ANOD BRUSHED DRILLED KIT COMPRISES OF: | |
| 500048 | 12mm | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED ANODISED TO 20 MICRONS | * Complete with seal strips, gaskets, side cladding and glass clamps | 1 x 3m Side Drilled Channel | |
| 500049 | 13.5mm | ANOD-BRUSHED | | | 1 x 3m Top Clip Bead | |
| 500050 | 15mm | ANOD-BRUSHED | | | 1 x 3m Side Cladding | |
| 500051 | 17.5mm | ANOD-BRUSHED | | | 1 x Clamp kit (consisting of 12 clamps) to suit specified glass thickness | |
| 500052 | 19mm | ANOD-BRUSHED | | | 1 x Spanner | |
| 500053 | 21.5mm | ANOD-BRUSHED | | | 1 x Dowel Chanel Joiners (Pair) | |
| 500424 | 12mm | MILL - FINISH | ALUM 6063 T6 | | | POSIGLAZE SIDE MILL FINISH DRILLED KIT COMPRISES OF: |
| 500425 | 13.5mm | MILL - FINISH | | | 1 x 3m Side Drilled Channel | |
| 500427 | 15mm | MILL - FINISH | | | 1 x 3m Top Bead | |
| 500428 | 17.5mm | MILL - FINISH | | | 1 x 3m Side Cladding | |
| 500430 | 19mm | MILL - FINISH | | | 1 x Clamp kit (consisting of 12 clamps) to suit specified glass thickness | |
| 500431 | 21.5mm | MILL - FINISH | | | 1 x Spanner | |
| | OVERALL LENGTH = 3000mm | ON REQUEST: POWDERCOAT ANOD NATURAL | | | 1 x Dowel Chanel Joiners (Pair) | |

BALUSTRADE SYSTEM COMPONENTS














Individual Parts – PosiGlaze



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|--|--|--|---|-------------------------------------|--|
| BASE DRILLED CHANNEL  | 300341 | 3000mm | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED Anodised TO 20 MICRONS | BASE DRILLED CHANNEL | BALUSTRADE CHANNEL SYSTEM COMPONENT | Internal & External  |
| | | GLASS THICKNESS: 12-21.5mm EXTRUSION SIZE: 72 x 119.5mm | ON REQUEST: POWDERCOAT | | | | |
| SIDE DRILLED CHANNEL  | 300342 | 3000mm | ANOD NATURAL | ALUM 6063 T6 - BRUSHED Anodised TO 20 MICRONS | SIDE DRILLED CHANNEL | BALUSTRADE CHANNEL SYSTEM COMPONENT | Internal & External  |
| | | GLASS THICKNESS: 12-21.5mm EXTRUSION SIZE: 74.5 x 119.5mm | | | | | |
| TOP SEAL STRIP  *Doesn't include bulb seal, please refer to Bulb Seal Gasket section for respective glass thicknesses | 301348 | 3000mm | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED Anodised TO 20 MICRONS | TOP SEAL STRIP *The top seal strip holds the gasket and is pressed onto the channel at the end of the installation. Covers the clamps from and prevents debris from entering the channel. | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| | 301349 | 3000mm | MILL - FINISH | | | | |
| | | | ON REQUEST: POWDERCOAT ANOD NATURAL | | | | |
| SIDE CLADDING  | 300419 | 3000mm | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED Anodised TO 20 MICRONS | SIDE CLADDING *As with the top seal strip it holds the gasket in place and covers the clamps from view. To be used with side drilled channel to cover the drill holes from view. Requires adhesive to hold flat surface against channel. | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| | 300420 | 3000mm | MILL - FINISH | | | | |
| | | | ON REQUEST: POWDERCOAT ANOD NATURAL | | | | |
| BOTTOM CLADDING  | 300417 | 3000mm | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED Anodised TO 20 MICRONS | BOTTOM CLADDING *Can be used with side fixed channel if required, gives an angled finish to the bottom of the channel. Clips into the grooves under the channel, will require adhesive for securing in place. | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| | 300418 | 3000mm | MILL - FINISH | | | | |
| | | | ON REQUEST: POWDERCOAT ANOD NATURAL | | | | |
| GLASS CLAMP  *Each kit contains 12 clamps (Inc. Clamps, x2 3m lengths bulb gasket, bars, bolts) | 300358 | 12mm | BLACK | PLASTIC | GLASS CLAMP *The clamps can fit glass thicknesses 1mm either way of nominal glass thickness i.e. 15mm glass clamps will suit 14 16mm glass. Included are the clamp bars, which sit into the top mould of the clamps and the clamp bolts, which screw into the bars and are then undone to hold the glass in place. These are undone and tightened each side allowing the glass alignment. 6m gasket to suit glass thickness. | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| | 300359 | 13.5mm | BLACK | | | | |
| | 300360 | 15mm | BLACK | | | | |
| | 300361 | 17.5mm | BLACK | | | | |
| | 300362 | 19mm | BLACK | | | | |
| | 300363 | 21.5mm | BLACK | | | | |
| | | | | | | | |

BALUSTRADE SYSTEM COMPONENTS







Individual Parts – PosiGlaze

| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|---|-------------------------------------|---|--|--------------------------------|--|
| DOWEL (CHANNEL JOINERS)  *Sold as a pair | 300860 | 30x9mm Dia | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED Anodised | CHANNEL JOINER *The dowels are used to allow for better aligning when joining channel sections together. | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| END CAPS  | 300505 | (PG120B) Base Fix | ANOD-BRUSHED | ALUM 6063 T6 - BRUSHED Anodised TO 20 MICRONS | END CAP *Stainless steel end caps cut to suit each option. An adhesive will need to be used to hold them in place. | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| | 300507 | (PG120S) Side Fix | ANOD-BRUSHED | | | | |
| | 300508 | (PG180S) Face Fix LH | ANOD-BRUSHED | | | | |
| | 300509 | (PG180S) Face Fix RH | ANOD-BRUSHED | | | | |
| | 300504 | (PG120B) Base Fix | MILL - FINISH | | | | |
| | 300506 | (PG120S) Side Fix | MILL - FINISH | | | | |
| | 300503 | (PG180S) Face Fix LH | MILL - FINISH | | | | |
| CUSTOM END CAPS  | 300510 | 1000 (L) x 72 x 1.2mm | ANOD-BRUSHED | | | | |
| | 300511 | 1000 (L) x 74 x 1.2mm | ANOD-BRUSHED | | | | |
| | | *For Stairs and angled cuts of Posi-Glaze Channel | ON REQUEST: POWDERCOAT ANOD NATURAL | | | | |
| SPANNER  | 301424 | Angled adjustment spanner | BLACK | STEEL | SPANNER *Steel spanner with angle to reach the clamp bolts to tighten/loosen the glass. | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| BULB SEAL GASKET  | 302089 | 12- 17.5mm | BLACK | RUBBER | BULB SEAL *Extra bulb seal gasket can be supplied in any length. The small bulb seal gasket suits 19 - 21mm glass, the large bulb seal gasket suits 12 - 17.5mm glass. | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| | 302090 | 19- 21.5mm | BLACK | | | | |
| | | *Sold as per (m) Length | | | | | |
| GASKET  | 300610 | 80 x 80 x 0.8mm | BLACK | FIBRE | CLAMP KIT GASKET | BALUSTRADE SYSTEM COMPONENT | Internal & External  |
| LINK RAIL LOCTITE 243  | 300961 | Suits S25 Rail | ADHESIVE | 50ML BOTTLE | TUBE LOCK ADHESIVE | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |

BALUSTRADE SYSTEM COMPONENTS

Balustrade Stiffener Brackets (For Aligning and Stiffening Panels)



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|--|--------|-------------------------|----------------------|---------------------|---|
| 90 DEGREE STIFFENER BRACKET (GLASS TO WALL)  | 300153 | 65x55x25mm GLASS THICKNESS: 12-15.5mm | SS | 2205 STAINLESS STEEL | STIFFENER BRACKET | FIXING COMPONENT | Internal & External  |
| | 300154 | 65x55x25mm GLASS THICKNESS: 17.2-21.5mm | SS | | | | |
| 90 DEGREE STIFFENER BRACKET (GLASS TO GLASS)  | 300151 | 75x50x25mm GLASS THICKNESS: 12-15.5mm | SS | 2205 STAINLESS STEEL | STIFFENER BRACKET | FIXING COMPONENT | Internal & External  |
| | 300152 | 88x55x25mm GLASS THICKNESS: 17.2-21.5mm | SS | | | | |
| 180 DEGREE STIFFENER BRACKET (GLASS TO GLASS)  | 300149 | 70x25mm GLASS THICKNESS: 12-15.5mm | SS | 2205 STAINLESS STEEL | STIFFENER BRACKET | FIXING COMPONENT | Internal & External  |
| | 300150 | 103x25mm GLASS THICKNESS: 17.2-21.5mm | SS | | | | |

NOTE: All brackets are supplied with a selection of gaskets to suit glass thickness.

BALUSTRADE RAIL SYSTEM






S25 Link Rail



- 25 x 21mm 2205 Stainless Steel.
- Suitable for 10mm or 12mm Glass Thickness.
- Rail Components available for 90 degree corners, adjustable corners (180 degrees to 90 degrees), stairway link connectors (Maximum 35 degrees), inline joiner.
- Wall mount brackets available including end caps.
- Satin Stainless Steel finish standard, can be Powdercoated upon request.

Compliance

















- Complies with NZS 4223.3.2016 and the latest amendment of New Zealand Building Code B1.

| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|---|------------------------|----------------------|--------------|--------------------------------|--|
| S25 LINK RAIL  | 300738 | 5800mm | SS | 2205 STAINLESS STEEL | LINK RAIL | BALUSTRADE LINK RAIL | Internal & External  |
| | | GLASS THICKNESS: 10-12mm OVERALL SIZE: 25 x 21mm | ON REQUEST: POWDERCOAT | | | | |
| S25 LINK RAIL WALL BRACKET (LEFT HAND)  | 300118 | Suits S25 Rail | SS | | | | |
| | | | ON REQUEST: POWDERCOAT | 2205 STAINLESS STEEL | WALL BRACKET | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| S25 LINK RAIL WALL BRACKET (RIGHT HAND)  | 301854 | Suits S25 Rail | SS | | | | |
| | | | ON REQUEST: POWDERCOAT | | | | |

BALUSTRADE RAIL SYSTEM

S25 Link Rail



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|---|------------------------------|----------------------|---------------------------------|--------------------------------|--|
| S25 LINK RAIL VERTICAL ADJUSTABLE JOINER  | 300863 | Suits S25 Rail | SS ON REQUEST: POWDERCOAT | 2205 STAINLESS STEEL | ADJUSTABLE JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| S25 LINK RAIL HORIZONTAL ADJUSTABLE JOINER  | 300862 | Suits S25 Rail | SS ON REQUEST: POWDERCOAT | 2205 STAINLESS STEEL | ADJUSTABLE HORIZONTAL JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| S25 LINK RAIL FIXED 90 DEGREE CORNER  | 300861 | Suits S25 Rail | SS ON REQUEST: POWDERCOAT | 2205 STAINLESS STEEL | 90 DEGREE CORNER CONNECTOR | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| S25 LINK RAIL INLINE JOINER  | 300852 | Suits S25 Rail | SS ON REQUEST: POWDERCOAT | 2205 STAINLESS STEEL | INLINE JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| S25 END CAP  | 300512 | Suits S25 Rail | SS ON REQUEST: POWDERCOAT | 2205 STAINLESS STEEL | END CAP | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| LINK RAIL LOCTITE 243  | 300961 | Suits S25 Rail | ADHESIVE | 50ML BOTTLE | TUBE LOCK ADHESIVE | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| S25 LINK RAIL RUBBER GASKET  | 302091 | Suits S25 Rail PER METRE LENGTH GLASS THICKNESS: 12mm | BLACK | RUBBER | RUBBER GASKET FOR S25 LINK RAIL | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| GRUB SCREW  | 301978 | M5x6mm | SS | 316 STAINLESS STEEL | GRUB SCREW | BALUSTRADE LINK RAIL FIXING | Internal & External  |

BALUSTRADE RAIL SYSTEM







S40 Link Rail



- 40 x 30mm 2205 Stainless Steel.
- Suitable for 12mm – 21.5mm Glass Thickness.
- Rubber gasket available to suit respective glass thicknesses.
- Rail Components available for 90 degree corners, adjustable corners (180 degrees to 90 degrees), stairway link connectors (Maximum 35 degrees), inline joiner.
- Wall mount brackets available including end caps.
- Satin Stainless Steel standard finish, can be Powdercoated upon request.

Compliance

















- Complies with NZS 4223.3.2016 and the latest amendment of New Zealand Building Code B1.

| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|---|------------------------|----------------------|--------------|--------------------------------|--|
| S40 LINK RAIL  | 300739 | 5800mm | SS | 2205 STAINLESS STEEL | LINK RAIL | BALUSTRADE LINK RAIL | Internal & External  |
| | | GLASS THICKNESS: 12 – 21.5mm OVERALL SIZE: 40 x 30mm | ON REQUEST: POWDERCOAT | | | | |
| S40 LINK RAIL WALL BRACKET (LEFT HAND)  | 300156 | Suits S40 Rail | SS | 2205 STAINLESS STEEL | WALL BRACKET | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | ON REQUEST: POWDERCOAT | | | | |
| S40 LINK RAIL WALL BRACKET (RIGHT HAND)  | 301855 | Suits S40 Rail | SS | 2205 STAINLESS STEEL | WALL BRACKET | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | ON REQUEST: POWDERCOAT | | | | |

BALUSTRADE RAIL SYSTEM







S40 Link Rail



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|--|------------------------|----------------------|---------------------------------|--------------------------------|--|
| S40 LINK RAIL VERTICAL ADJUSTABLE JOINER  | 300868 | Suits S40 Rail | SS | 2205 STAINLESS STEEL | ADJUSTABLE VERTICAL JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | ON REQUEST: POWDERCOAT | | | | |
| S40 LINK RAIL HORIZONTAL ADJUSTABLE JOINER  | 300867 | Suits S40 Rail | SS | 2205 STAINLESS STEEL | ADJUSTABLE HORIZONTAL JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | ON REQUEST: POWDERCOAT | | | | |
| S40 LINK RAIL FIXED 90 DEGREE CORNER  | 300866 | Suits S40 Rail | SS | 2205 STAINLESS STEEL | 90 DEGREE CORNER CONNECTOR | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | ON REQUEST: POWDERCOAT | | | | |
| S40 LINK RAIL INLINE JOINER  | 300869 | Suits S40 Rail | SS | 2205 STAINLESS STEEL | INLINE JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | ON REQUEST: POWDERCOAT | | | | |
| S40 END CAP  | 300513 | Suits S40 Rail | SS | 2205 STAINLESS STEEL | END CAP | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | ON REQUEST: POWDERCOAT | | | | |
| LINK RAIL LOCTITE 243  | 300961 | Suits S40 Rail | ADHESIVE | 50MM BOTTLE | TUBE LOCK ADHESIVE | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | | | | | |
| S40 LINK RAIL RUBBER GASKET  | 302092 | Suits S40 Rail | BLACK | RUBBER | RUBBER GASKET FOR S40 LINK RAIL | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | PER METRE LENGTH GLASS THICKNESS: 12-13.5mm | | | | | |
| S40 LINK RAIL RUBBER GASKET  | 302093 | Suits S40 Rail | BLACK | RUBBER | RUBBER GASKET FOR S40 LINK RAIL | BALUSTRADE LINK RAIL FIXING | Internal & External  |
| | | PER METRE LENGTH GLASS THICKNESS: 12-15mm | | | | | |

BALUSTRADE RAIL SYSTEM

S40 Link Rail

| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|--|--------|---------------------|---------------------------------|--------------------------------|--|
| S40 LINK RAIL RUBBER GASKET  | 302094 | Suits S40 Rail | BLACK | RUBBER | RUBBER GASKET FOR S40 LINK RAIL | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | PER METRE LENGTH GLASS THICKNESS: 13-16mm | | | | | |
| S40 LINK RAIL RUBBER GASKET  | 302095 | Suits S40 Rail | BLACK | RUBBER | RUBBER GASKET FOR S40 LINK RAIL | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | PER METRE LENGTH GLASS THICKNESS: 16-19mm | | | | | |
| GRUB SCREW  | 301978 | M5x6mm | SS | 316 STAINLESS STEEL | GRUB SCREW | BALUSTRADE LINK RAIL FIXING | Internal & External  |
| | | | | | | | |

BALUSTRADE RAIL SYSTEM

Edgetec® 220 Link Rail



Aluminium LinkRail 38x30mm – For 12mm and 15mm Glass

- 38 x 30mm Aluminium Link Rail.
- Available in Natural Anodised Finish 20 microns as standard or Silver Frost powdercoat. Special colours on request (Powdercoating or Anodising).
- Rubber gasket available to suit 12mm or 15mm glass thicknesses.
- Rail Components available for 90 degree corners, adjustable corners (180 degrees to 90 degrees), stairway link connectors (Maximum 35 degrees), inline joiner.
- Wall mount brackets available including end caps.









Compliance

- Complies with NZS 4223.3.2016 and the latest amendment of New Zealand Building Code B1.

BALUSTRADE RAIL SYSTEM

Edgetec® 220 Link Rail



















| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|--|------------------------|-----------|--|--------------------------------|--|
| EDGETEC® 220 LINK RAIL FULL LENGTH  | 300728 | 5800mm | ANOD – Natural | ALUM 6063 | LINK RAIL | BALUSTRADE LINK RAIL | Internal & External  |
| | 300729 | 5800mm | SILVER FROST | | | | |
| | 300727 | 5800mm | MILL FINISH | | | | |
| | | GLASS THICKNESS: 12-15mm OVERALL SIZE: 38 x 30mm | ON REQUEST: POWDERCOAT | | | | |
| EDGETEC® 220 LINK RAIL HALF LENGTH  | 300725 | 2900mm | ANOD – Natural | ALUM 6063 | LINK RAIL | BALUSTRADE LINK RAIL | Internal & External  |
| | 300726 | 2900mm | SILVER FROST | | | | |
| | 300724 | 2900mm | MILL FINISH | | | | |
| | | (Half Length) GLASS THICKNESS: 12-15mm OVERALL SIZE: 38 x 30mm | ON REQUEST: POWDERCOAT | | | | |
| EDGETEC® 220 LINK RAIL RUBBER GASKET  | 300593 | 2900mm | BLACK | RUBBER | RUBBER GASKET FOR EDGETEC® 220 LINK RAIL | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | GLASS THICKNESS: 12mm | | | | | |
| EDGETEC® 220 LINK RAIL RUBBER GASKET  | 300594 | 2900mm | BLACK | RUBBER | RUBBER GASKET FOR EDGETEC® 220 LINK RAIL | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | GLASS THICKNESS: 15mm | | | | | |
| EDGETEC® 220 LINK RAIL INLINE JOINER  | 300847 | 80x22.8x5mm | MILL | ALUM 6063 | 180 DEGREE STRAIGHT JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | | | | | |
| EDGETEC® 220 LINK RAIL 90 DEGREE JOINER  | 300848 | 50x50x5mm | MILL | ALUM 6063 | 90 DEGREE CORNER JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | | | | | | | |
| EDGETEC® 220 END CAP  | 300493 | 38.4 x 30.4mm | ANOD – Natural | ALUM 6063 | END CAP | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | 300494 | 38.4 x 30.4mm | SILVER FROST | | | | |
| | 300492 | 38.4 x 30.4mm | MILL | | | | |
| | | Suits Edgetec® 220 Rail (Component) | ON REQUEST: POWDERCOAT | | | | |
| EDGETEC® 220 LINK RAIL FIXED 90 DEGREE CORNER  | 301985 | Suits Edgetec® 220 Rail | SILVER FROST | ALUM 6063 | 90 DEGREE CORNER CONNECTOR | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | 301986 | Suits Edgetec® 220 Rail | MILL | | | | |
| | | (Component) | ON REQUEST: POWDERCOAT | | | | |

BALUSTRADE RAIL SYSTEM

Edgetec® 220 Link Rail



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|-------------------------------------|------------------------|---------------------|------------------------------|--|--|
| EDGETEC® 220 LINK RAIL HORIZONTAL ADJUSTABLE JOINER  | 301987 | Suits Edgetec® 220 Rail | SILVER FROST | ALUM 6063 | ADJUSTABLE HORIZONTAL JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | 301988 | Suits Edgetec® 220 Rail | MILL | | | | |
| | | (Component) | ON REQUEST: POWDERCOAT | | | | |
| EDGETEC® 220 LINK RAIL VERTICAL ADJUSTABLE JOINER  | 301989 | Suits Edgetec® 220 Rail | SILVER FROST | ALUM 6063 | ADJUSTABLE VERTICAL JOINER | BALUSTRADE LINK RAIL COMPONENT | Internal & External  |
| | 301990 | Suits Edgetec® 220 Rail | MILL | | | | |
| | | (Component) | ON REQUEST: POWDERCOAT | | | | |
| EDGETEC® 220 WALL BRACKET (LEFT HAND)  | 301003 | 120 x 45mm | SILVER FROST | ALUM 6063 | WALL BRACKET | BALUSTRADE LINK RAIL COMPONENT *For attaching to posts or structures | Internal & External  |
| | 301004 | 120 x 45mm | MILL | | | | |
| | | Suits Edgetec® 220 Rail (Component) | ON REQUEST: POWDERCOAT | | | | |
| EDGETEC® 220 WALL BRACKET (RIGHT HAND)  | 301005 | 120 x 45mm | SILVER FROST | ALUM 6063 | WALL BRACKET | BALUSTRADE LINK RAIL COMPONENT *For attaching to posts or structures | Internal & External  |
| | 301006 | 120 x 45mm | MILL | | | | |
| | | Suits Edgetec® 220 Rail (Component) | ON REQUEST: POWDERCOAT | | | | |
| EDGETEC® 220 WALL BRACKET POST END MOUNT  | 301002 | 100 x 65mm | SILVER FROST | ALUM 6063 | WALL BRACKET | BALUSTRADE LINK RAIL COMPONENT *For attaching to posts or structures | Internal & External  |
| | 301149 | 100 x 65mm | MILL | | | | |
| | | Suits Edgetec® 220 Rail (Component) | ON REQUEST: POWDERCOAT | | | | |
| EDGETEC® 220 WALL BRACKET POST END MOUNT* *Suits AP65 Series Aluminium Post  | 301991 | 60 x 46mm | SILVER FROST | ALUM 6063 | POST END MOUNT FOR AP65 | BALUSTRADE LINK RAIL COMPONENT *For attaching to posts or structures | Internal & External  |
| | 301992 | 60 x 46mm | MILL | | | | |
| | | Suits Edgetec® 220 Rail (Component) | ON REQUEST: POWDERCOAT | | | | |
| SCREW  | 301993 | 6G x 1/4" Sq | SS | 304 STAINLESS STEEL | SCREW | PAN HEAD SCREW SUITS COMPONENT 300847 300848 301985 301986 301003 301004 301005 301006 301002 301149 301991 301992 | Internal & External  |
| | | GLASS THICKNESS: 12mm, 15mm | | | | | |
| SILICONE – STRUCTURAL GLAZING  | 300011 | V60 | ADHESIVE | CARTRIDGE | SILICONE | FIXING COMPONENT | Internal & External  |
| | | | | | | | |

BALUSTRADE FIXING COMPONENTS – BASE FIX PG120B

Concrete and Steel Substrates (Domestic and Commercial Applications)

CONCRETE FIXING – BASE FIX

A,B,E,C3 OCCUPANCY TYPE



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|--|----------|---------------------|-----------------------------|------------------|-------------------------|
| THREADED ROD FOR CHEMICAL ANCHOR | 501164 | M10 x 110mm Threaded Rod M12 x 24 x 2.5mm Washer (Round) M10 Nut | SS | 316 STAINLESS STEEL | THREADED ROD / WASHER / NUT | FIXING COMPONENT | Internal & External |
| HILTI HIT-HY 200 MAX CHEMICAL ANCHOR | 300003 | 330ml | ADHESIVE | CARTRIDGE | CHEMICAL ANCHOR | | |

CONCRETE FIXING – BASE FIX

C1/C2, D OCCUPANCY TYPE



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|--|----------|---------------------|--------------------------------------|------------------|-------------------------|
| THREADED ROD FOR CHEMICAL ANCHOR | 500256 | M12 x 125mm Threaded Rod M12 x 24 x 2.5mm Washer (Round) M12 nut | SS | 316 STAINLESS STEEL | THREADED SLEEVE / WASHER / HEX SCREW | FIXING COMPONENT | Internal & External |
| HILTI HIT-HY 200 MAX CHEMICAL ANCHOR | 300003 | 330ml | ADHESIVE | CARTRIDGE | CHEMICAL ANCHOR | | |

STEEL FIXING – BASE FIX

ALL OCCUPANCY TYPES



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|--|--------|---------------------|--------------------------|------------------|-------------------------|
| HEX SCREW <p>*Check length for application</p> | 500257 | M10 x 35mm | SS | 316 STAINLESS STEEL | HEX SCREW / WASHER / NUT | FIXING COMPONENT | Internal & External |
| | 501267 | M10 x 40mm | SS | | | | |
| | 501268 | M10 x 50mm | SS | | | | |
| | | INCLUDES: X2 M12 x 24 x 2.5mm Washer (Round) M10 Nut | | | | | |

BALUSTRADE FIXING COMPONENTS – SIDE FIX PG120S/PG180S

Concrete, Steel and Timber Substrates (Domestic and Commercial Applications)

CONCRETE FIXING – SIDE FIX

ALL OCCUPANCY TYPES



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|--|----------|---------------------|-----------------------------|------------------|-------------------------|
| THREADED ROD FOR CHEMICAL ANCHOR | 500255 | M10 x 190mm Threaded Rod M12 x 24 x 2.5mm Washer (Round) M10 Nut | SS | 316 STAINLESS STEEL | THREADED ROD / WASHER / NUT | FIXING COMPONENT | Internal & External |
| HILTI HIT-HY 200 MAX CHEMICAL ANCHOR | 300003 | 330ml | ADHESIVE | CARTRIDGE | CHEMICAL ANCHOR | | |

STEEL FIXING – SIDE FIX

ALL OCCUPANCY TYPES



| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|---|--------|--|--------|---------------------|--------------------------|------------------|-------------------------|
| HEX SCREW *Check length for application | 500257 | M10 x 35mm | SS | 316 STAINLESS STEEL | HEX SCREW / WASHER / NUT | FIXING COMPONENT | Internal & External |
| | 501267 | M10 x 40mm | SS | | | | |
| | 501268 | M10 x 50mm | SS | | | | |
| | | INCLUDES: X2 M12 x 24 x 2.5mm Washer (Round) M10 Nut | | | | | |

TIMBER FIXING – SIDE FIX

A, B, E, C3, C1/C2, D OCCUPANCY TYPE

















| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|---|--------|---------------------|-----------------------|-------------|------|
| COACH SCREW | 500632 | M10 x 120mm Coach Screw M10/12x24x2.5mm Washer (Round) | SS | 316 STAINLESS STEEL | COACH SCREW / WASHER | | |
| HEX BOLT *Check length for application | 500259 | M10 x 130mm Hex Bolt M12 x 24 x 2.5mm Washer (Round) M12 Washer 50 x 50mm x 5mm (Square) M10 Nut | SS | 316 STAINLESS STEEL | HEX BOLT WASHER / NUT | | |

BALUSTRADE FIXING INDIVIDUAL COMPONENTS

Fixings: Rods, Anchors, Screws, Washers, Nuts







To suit Concrete, Steel and Timber Substrates (Domestic and Commercial Applications)

| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|---------------|----------|---------------------|-----------------|------------------|--|
| M10 x 110mm THREADED ROD  | 301500 | M10 x 110mm | SS | 316 STAINLESS STEEL | THREADED ROD | FIXING COMPONENT | Internal & External  |
| | | | | | | | |
| HILTI HIT-HY 200 MAX CHEMICAL ANCHOR  | 300003 | 330ml | ADHESIVE | CARTRIDGE | CHEMICAL ANCHOR | FIXING COMPONENT | Internal & External  |
| | | | | | | | |
| WASHER M12X24X2.5  | 301603 | M12x24x 2.5mm | SS | 316 STAINLESS STEEL | WASHER | FIXING COMPONENT | Internal & External  |
| | | | | | | | |
| M10 NUT  | 301025 | M10 Nut | SS | 316 STAINLESS STEEL | NUT | FIXING COMPONENT | Internal & External  |
| | | | | | | | |
| M10 HEX SCREW  | 301303 | M10 x 35mm | SS | 316 STAINLESS STEEL | HEX SCREW | FIXING COMPONENT | Internal & External  |
| | 301880 | M10 x 40mm | SS | | | | |
| | 302013 | M10 x 50mm | SS | | | | |
| | | | | | | | |
| HEX SCREW M12 X 35MM  | 301305 | M12 x 35mm | SS | 316 STAINLESS STEEL | HEX SCREW | FIXING COMPONENT | Internal & External  |
| | | | | | | | |
| M12 NUT  | 301028 | M12 Nut | SS | 316 STAINLESS STEEL | NUT | FIXING COMPONENT | Internal & External  |

BALUSTRADE FIXING INDIVIDUAL COMPONENTS

Fixings: Rods, Anchors, Screws, Washers, Nuts

To suit Concrete, Steel and Timber Substrates (Domestic and Commercial Applications)

| Product | Model | Sizes mm | Finish | Material | Type | Application | Area |
|--|--------|--------------------------|--------|---------------------|-------------|------------------|---|
| M10 COACH SCREW  | 301837 | M10 x 180mm | SS | 316 STAINLESS STEEL | COACH SCREW | FIXING COMPONENT | Internal & External  |
| | 301926 | M10 x 120mm | SS | | | | |
| M12 WASHER 50MM X 50MM X 5MM  | 302098 | M12 Washer 50 x 50 x 5mm | SS | 316 STAINLESS STEEL | WASHER | FIXING COMPONENT | Internal & External  |
| M10 HEX BOLT  | 300528 | M10 x 240mm | SS | 316 STAINLESS STEEL | HEX BOLT | FIXING COMPONENT | Internal & External  |
| | 300527 | M10 x 130mm | SS | | | | |